


JDENERGY


eBlock 418A


POTENTIAL FOR GREATNESS EXCELLENCE IN STORAGE




Intelligent energy block eBlock-418A
209kW/418kWh | Energy Storage System

 Economically efficient

 Ultimate safety

 Grid friendly

 Intelligent operation and maintenance

■ **Economically efficient**

- No Parallel Design on DC Side, 100% DOD.
- High Efficiency Liquid Cooling Design.
- Conversion Efficiency $\geq 90\%$ on AC Side.

■ **Ultimate Safety**

- High-Temperature-Resistant Material that can Meet 2h Fire Resistance as the Shell.
- Integration of BMS and PCS, Realizing Fast and Comprehensive Protection.

■ **Grid friendly**

- Multiple Control Modes including Primary Frequency Control (PFC), Peak Shaving and Valley Filling, and High-Speed Scheduling.
- Heterogeneous Cluster Control Platform, achieving High-Speed Dispatching of Thousands of eBlocks at 100ms level.

■ **Intelligent operation and maintenance**

- Multi-parallel Connection, Realizing Flexible Expansion and Block Building of Energy Storage Power Station.
- Statistical Analysis of Big Data, Predicting Battery Cell Lifespan, Warning of Battery Cell Failures.

SYSTEM DATA

Cell Type	LFP 3.2V/314Ah
Battery grouping method	416S1P
Battery capacity	418kWh
Battery voltage range	1164.8~1497.6V
AC rated power	209kW (215kW Derating)
Maximum system efficiency	$\geq 90\%$
Depth Of Discharge	100% DOD
communication interface	LAN
AC current distortion rate	<3%
DC component	< 0.5% pn
Number of cycles	≥ 7000 Cycles
System protection level	IP55
Working temperature	-35°C~55°C (45°C~55°C derating)
Working humidity	0%RH ~ 95%RH (No condensation)
Noise	< 80db
Altitude	≤ 2000 m
Thermal management methods	Liquid cooling (battery)
Certification	UL9540 UL9540A FCC Part 15B NFPA69 NEPA855 UL1973 UL1741

MECHANICAL PARAMETER

Dimensions (L*W*H)	1400mm*1300mm*2350mm
Total Weight	3800Kg
Installation mode	modular steel structure base

PCS DATA PCS/PCS-2000G2

System rated efficiency	$\geq 98\%$
Charging and discharging switching time	<100ms
Communication interface	LAN
Protection grade	IP65
Cooling method	Air cooling
Operation temperature	-40°C~60°C
Relative humidity	0~95%RH
Max. working altitude	≤ 2000 m
Noise	<80dB
Size (L * W * H)	630*1050*250
Weight	110kg
Certification	UL1741 IEEE1547

DC SIDE PARAMETERS

DC voltage range	1026~1500V
DC rated voltage	1263V
Max. DC current	209.5A
Max. DC power	258kW

AC SIDE PARAMETERS

AC rated power	215kW
AC rated current	180A
Rated grid voltage	690V
LVRT/HVRT	Yes
Grid Frequency	50/60Hz

Xi'an JDenergy Co., Ltd.

☎ 029-84845916 / 400-1336580

🌐 www.jdenergy.com

📍 Headquarters Address: No. 25, West Section of First Biyuan Road, High-tech Zone, Xi' an City, Shaanxi, China